

Published on EMAC Inc. (https://www.emacinc.com)

Source URL: https://www.emacinc.com/content/ahp-1122

AHP-1122



12.1" 500 Nits XGA LED Backlight 12.1" 1000 Nits XGA LED Backlight

Onboard Intel® Atom™ D510 1.66 GHz

System memory 1 GB expandable up to 2 GB of DDR2

Compact Flash socket

Dual 10/100/1000Base-TX

Fanless and ultra-low power consumption

PCIe Mini Socket x 2

RFID / WiFi (Optional)

Slim Design: 64mm

The AHP-1122 operator panel is an Intel® Atom™ D510 1.66 GHz processor computer that is designed to serve as a human machine interface (HMI). It is a PC-based system with 12.1" color TFT LCD display, onboard Ethernet controller, multi-COM port interfaces and an audio controller. With a built-in CompactFlash socket, the AHP-1122 is as compact and user friendly as a multi-function computer. In addition, its "fit anywhere" design makes it very flexible and able to be used in many different kinds of installations. It can be VESA 75 wall mounted. For system integrators, this simple, complete, compact and highly integrated system let you easily build an operator panel into your applications. Common industrial applications include factory automation systems, precision machinery, and production process control. It is also suitable for many non-industrial applications, including vending machine, and car park automation. Our operator panel is a reliable, cost affective solution to your application's processing requirements.

Specifications Paner 1 C 1 ype.

Eroland DDC

Processor Processor.

Intel® AtomTM D510

Clock Speed:
1.66 GHz
Real Time Clock:
Memory Primary riash:
Supports CompactFlash™
Memory Misc.:
Memory: DDR2 SODIMM, Up to 2 GB
Primary I/O Viuco Out.
12.1
Ethernet:
Dual 10/100/1000 Base-TX Ethernet interface
USB:
4x USB 2.0
Serial Ports:
1x RS-232/422/485
1x RS-232
Watchdog: Primary I/O Misc.:
-
Additional I/O: External VGA port
HDD: One internal 2.5" SATA Interface
Touchscreen
Type: 5-wire analog resistive
Light Transmission: >80%
Controller: Integrated in Processor
Software Driver: Supports WES, CE, Linux
Software Driver. Supports WES, CE, Emux
Lifetime: 35 million activations
Secondary I/O
Keypad:
PS/2:
Expansion Bus.
Dual Mini PCIe sockets (Wireless, Bluetooth, RFID capability)
Analog
D/A:
Dimensions Dimensions.
Difficultions. $12.5 \times 9.5 \times 2.5$ in
Weight: 4.2 kg
T.2 NS
Power Requirements

High Operating Temperature:
50 C
Environmental Misc.:
Relative Humidity: 10 ~ 90% @ 40 ° C (non-condensing)
Shock (Operating): 20 G peak acceleration (11 ms. duration)
EMC: CE, FCC Class A approved
Pricing Product variations:
AHP-1122HT
1.6GHZ ATOM D510 PANEL PC W/ TOUCH, 1GB RAM
\$1,103.00
Parent Product:
AHP-1122ST
1.6GHZ ATOM D510 PANEL PC W/ TOUCH, 1GB RAM(1000 NITS)
\$1,371.00
Parent Product:
Source URL: https://www.emacinc.com/content/ahp-1122

Environmental

Low Operating Temperature:

0 C