

Published on EMAC Inc. (https://www.emacinc.com)

Source URL: https://www.emacinc.com/content/pcm-9562

PCM-9562



Embedded Intel® Atom Fanless N450 or D510 (Dual Core) Processor

Supports DDR2 memory

Supports Dual Independet Display

Supports Up to 3 Gig Ethernets

Supports Up to 6 Serial ports

Supports 8 USB 2.0 ports

Supports 3 SATA drives

Supports PC/104+, PCI & Mini PCI Express Expansion

Supports +5 V and +12 V power; or single +5 V power

Wide Temperature Version Available

The PCM-9562 is centered on the low power Intel® Atom Single Core N450 or Dual Core D510 processor which supports enhanced Intel "SpeedStep" technology and uses Intel's N450/D510 chipset. This chipset is ideal for embedded computing and provide an optimized onboard integrated graphics solution. "SpeedStep" technology intelligently focuses system power where the CPU needs it and automatically regulates power usage to minimize power consumption. The PCM-9562's design is based on the EBX form factor and provides expansion support via PC/104+, a PCI slot and a Mini PCI Express slot. The EBX form factor also provides convenient connector layout for easy assembly, more efficient cable connections, and better overall embedded system integration. This compact unit (only 8" x 5.75") offers all the functions of a rack type industrial computer, but still fits in the space of a CD-ROM drive. On-board features include: six serial ports, eight USB (Universal Serial Bus) 1.1/2.0 ports, three Gig Ethernet ports, an Audio port and a PS/2 keyboard/mouse interface. The built-in high-speed SATA Hard Driver controller supports a maximum transfer rate of 300MB per second. Up to three drives can be connected, including large bard disks, CD-ROM drives, and tape backup drives. **Flash Disk and Memory not included.**

Single Deard Computers > 1 GHz Processor Embedded Intel Atom N450/D510 (Dual Core) Clock Speed: 1.66 GHz Real Time Clock: Processor Misc.: Chipset: N450/D510

L2 Cache: 512 KB/1 MB

Memory BIOS/ BOOlloader: AMI 16 Mbit Primary Flash: 1x CompactFlashTM card Type I/II Primary I/O Intel Dual Display CRT/LCD up to 224 MB shared Audio: Realtek ALC888 HD codec with AC97 Line-in/Line-out/Mic-in Ethernet: IEEE 802.3u 10/100/1000 Base-T with 1x RJ45 connector USB: 8x USB 2.0 Serial Ports: 3x RS-232 2x RS-232/422/485 1x Parallel SPP/EPP/ECP Watchdog: Primary I/O Misc.: SATA Interface: Three SATA Channels supporting 3 drives

Optional Serial Port: 1x RS232 port

Ethernet Chipset:

- LAN1 Intel 82567
- LAN2 Intel 82583V
- ° LAN3 Intel 82583V (Optional Contact Sales Minimum Order Quantity is required.)

Ll I I Ott. Keypad: PS/2:

Analog on A.D. D/A:

Dimensions B × 5.75 in Weight: 850 g Form Factor: Full EBX

Power Requirements Power Ivinse.. Power Management APM 1.2, ACPI 3.0 supported

Power Requirements: AT / ATX (Both AT/ATX can support ACPI)

- $^\circ~$ AT: 12V ±10% only
- $^{\rm O}\,$ ATX: 12V ±10%, 5VSB ±5% (5V stand-by is for auto power off function)
- Maximum:
 - PCM-9562N: 13.9W (1159 mA @ 12V, 6 mA @ 5 VSB)
 - PCM-9562D: 16.9W (1404 mA @ 12V, 8 mA @ 5 VSB)

Typical:

- PCM-9562N: 10.8W (893 mA @ 12V, 8 mA @ 5 VSB)
- PCM-9562D: 13.6W (1130 mA @ 12V, 10 mA @ 5 VS)

Environmental Low Operating Temperature: 0 C High Operating Temperature: 60 C Environmental Misc.: Temperature PCM-9562NZ: - 20 to + 80°C

PCIVE-2502N ATom 1.6GHz N450 Fanless SBC w/video, Dual GIG LAN (one remaining in stock) \$324.00 Parent Product:

PCM-9562D ATOM 1.6GHZ D510 DUAL CORE SBC W/Video, DUAL GIG LAN \$319.00 Parent Product:

PCM-9562NZ

ATOM 1.6GHZ N450 Wide temp SBC W/Video, DUAL GIG LAN, 1 GB RAM \$474.00 Parent Product:

Wiring Kits: PCM-10586-9562E Wiring Kit for the PCM-9562 \$55.00

Source URL: https://www.emacinc.com/content/pcm-9562