

PPC-150T



Processor

- DMP Vortex86DX3 1 GHz
- DMP Vortex86DX2 933 MHz

512MB / 1GB / 2GB DDRII RAM Onboard

2x Serial Ports (RS-232/422/485)

- 75x RS232 Serial ports (optional)

3x USB 2.0 Ports

Integrated 10/100Mbps Ethernet

- 10/100/1000 BaseT Gig Ethernet(optional)

HD Audio-Realtek ALC262 CODEC

SATA Slim DOM

Compact Flash Type I/II slot or SD slot(optional, removes compact flash)

15" XGA TFT LCD, 1024x768, Analog Resistive

Touch Screen

- ?Analog resistive
- Capacitive (up to 10 points)

Wi-Fi (Optional)

DOS, Linux, Windows XP, Windows Embedded Standard 2009 or Windows Embedded Standard 7

Voltage: +12VDC to +24VDC

Operating Temperature: -0° - 50° C

- ?Optional wide operating Temperature: -20°C to 60°C

0% ~ 90% Relative Humidity, Non-Condensing

Weight: 3.8 kg

Dimensions: 354.85 x 208.85 x 55 mm (13.97 x 11.06 x 2.16 inches)

15" Panel PC- PPC-150T, comes with 15" industrial LCD and touchscreen(Analog Resistive or Capacitive), IP65 standard front panel, waterproof and dustproof, and wide operating temperature range from 0°C to 50°C (32°F to 122°F) or optional -20°C to 60°C (-4°F to 140°F) metal chassis with compact design.

Specifications

Panel PC type.

Enclosed DDG

Processor

Processor.

Vortex86DX3

Clock Speed:

1 GHz

Real Time Clock:

Processor Misc.:

Processor:

DMP Vortex86DX2 933 MHz

DMP Vortex86DX3 1 GHz

Memory

RAM type.

DDR2 Onboard

Primary Flash:

Compact Flash or SATA DOM

Memory Misc.:

SD slot (Optional)

Primary I/O

HD Audio-Realtek ALC262 CODEC

Ethernet:

Integrated 10/100Mbps Ethernet

USB:

USB Ports (Version 2.0) x 3

Serial Ports:

2x RS-232 / 422 / 485 (5x RS232 optional)

Watchdog:

Primary I/O Misc.:

Ethernet-

POE (Optional)

Giga Ethernet (optional)

WIFI (Optional)

Secondary I/O

Keypad:

PS/2:

Touch:

Analog Resistive

Analog on

D/A:

Dimensions

13.97 × 8.22 × 2.16 in

Weight:

4 kg

Power Requirements

Voltage: +12VDC / +24VDC

Environmental

Low Operating Temperature:

0 C

High Operating Temperature:

50 C

Upper Operating Humidity:

90%

Environmental Misc.:

Optional Wide temp: -20°C to 70°C

Pricing
Product variations:

PPC-150T-D2N4N

15" Panel PC w/1GB Memory / 3USB / AUDIO / LAN / 2COM / DC12~24V / 0° to 50°

\$878.00

Order:

0

Parent Product:

PPC-150T-D2W4N

15" Panel PC w/1GB Memory / 3USB / AUDIO / LAN / 2COM / DC12~24V / -20° to 60°

\$928.00

Order:

0

Parent Product:

PPC-150T-D2W5N-GE

15" Panel PC w/2GB Memory / 3USB / AUDIO / LAN / GigaLAN /2COM / DC12~24V / -20° to 60°

\$953.00

Order:

0

Parent Product:

Disk Interface:

CompactFlash Type II socket

SD socket

or SATA Slim DOM

Source URL: <https://www.emacinc.com/content/ppc-150t>