

Published on EMAC Inc. (https://www.emacinc.com)

Source URL: https://www.emacinc.com/content/sib-eb30v-c

SIB-EB30V-C



Vortex86DX2 933MHz

1GB/2GB DDR2 RAM Onboard

Up to 4x RS-232

3x USB 2.0 Ports

1x 10/100 Ethernet

1x SD slot

AMI BIOS

1x SATA 2.0

2.5" SATA HDD/SSD Support

SATA DOM Support

15V 1.5A Wall Mount Power supply Included.

1x VGA

HD Audio Line Out

Mic Input (Optional)

TTL Level RS-232 (Optional)

Auto Power On

Wifi (Optional)
115 x 115 x 35mm
DC +8V ~ +15V
5 ~50° C
The EB-3330 & EB-3332 series is a revolutionary device which is especially designed for limited physical space and temperature concerns. No matter you are in a jammed office, a crowded place, or public transportation, the EB-3330 & EB-3332 can be easily integrated with a VESA LCD to bring it to access at any time. It can be attached to any VESA mounting fixture; allowing it to be securely mounted onto desks, walls, or buildings, and thereby optimizes your work area. It can also be attached directly to any size LCD for a mobile system for the use at trade shows, presentations, promotions, etc. Unlike traditional portable laptop design, the EB-3330 & 3332 series can be used with a large size LCD. Furthermore, with FANLESS design, the EB-3330 & EB-3332 series is ideal to be used in the environment where temperature demand is critical. So, if you are looking for a device that is able to provide you with more mobility & space but at the same time uses less power consumption, then the EB-3330 & 3332 series will be surely meet your need. The VESA® FDMI TM Standard defines mounting interfaces, hole patterns and associated cable/power supply locations for LCD monitors, plasma displays and other flat panel devices. The EB 3330 & 3332 series is designed to fit this standard to make monitor attachment quickly and easily. Specifications Plocessor.
Vortex86DX2
Clock Speed:
933 MHz
Real Time Clock:
Memory Raivi 1 ype.
DDR2 (Up to 2GB DDR2)
BIOS/ Bootloader:
AMI BIOS
Primary Flash:
1x 2.5 inch SATA HDD/SSD or DOM
Secondary Flash:
1x SD slot
Primary I/O
VGA
Audio:
HD Audio Line Out
Ethernet:
1x 10/100 Ethernet
USB:
3x USB 2.0 Ports
Serial Ports:
Up to 4x RS-232
Watchdog:
Ll I Fort.

Ultra Low Power

Fanless Design

Keypad: PS/2:
Expansion Bus.
Internal USB for WIFI
Analog A/D.
D/A:
Dimensions Dimensions.
4.5 × 4.5 × 1.38 in
Weight:
510 g
Power Requirements Voltage. 8 V
Power Misc.:
DC +8 ~ +15V
Environmental Low Operating Temperature: 5 C
High Operating Temperature: 50 C
Pricing V-201-R EB-3330-C2, Vortex86DX2 933MHz, 1GB RAM, 2x RS-232, 3xUSB2, 1xLAN, VGA \$194.00 Order: O Parent Product:
SIB-EB30V-401-R EB-3330-C4, Vortex86DX2 933MHz, 1GB RAM, 4x RS-232, 3xUSB2, 1xLAN, VGA \$209.00 Order: 0 Parent Product:
SIB-EB32V-201-R EB-3332-C2, Vortex86DX2 933MHz, 2GB RAM, 2x RS-232, 3xUSB2, 1xLAN, VGA \$245.68 Order: 0 Parent Product:

SIB-EB32V-401-R

Parent Product:	
Power Supply:	
DC +8V ~ +15V (Included Wall Mount 15V 1.5A power supply)	
Disk Interface:	
1x SATA 2.0	
Wireless:	
Wifi (Optional)	
Source URL: https://www.emacinc.com/content/sib-eb30v-c	

EB-3332-C4, Vortex86DX2 933MHz, 2GB RAM, 4x RS-232, 3xUSB2, 1xLAN, VGA

\$260.49 Order: