

Published on EMAC Inc. (https://www.emacinc.com)

Source URL: https://www.emacinc.com/content/sib-a6523

SIB-A6523



Intel® AtomTM N2600 Dual Core 1.6GHz

2GB DDR3 SODIMM

1x RS-232/422/485, 3x RS-232

4x USB 2.0 Ports

2x Gigabit Ethernet with RJ-45 connector

1x VGA

1x 2.5' SATA 2 (3.0Gb/s) HDD drive bay

1x Mini Card Slot

CFastTM slot x 1 (w/ cover protection)

Power ON/OFF

Power LED x 1, Hard disk active LED x 1, CFastTM slot x 1, Antenna hole x 2

DC power input DC 9-30V w/ 3-pin terminal block

8.35"(W) x 3.1"(H) x 2.25"(D)

Operating Temperature With W/T HDD:

No Airflow: $-22^{\circ}F \sim 149^{\circ}F (-30^{\circ}C \sim 65^{\circ}C)$

Ambient with Airflow: $-22^{\circ}F \sim 158^{\circ}F (-30^{\circ}C \sim 70^{\circ}C)$

Operating Temperature With W/T Cfast:

No Airflow: $-40^{\circ}F \sim 131^{\circ}F (-40^{\circ}C \sim 55^{\circ}C)$

Ambient with Airflow: $-40^{\circ}F \sim 140^{\circ}F (-40^{\circ}C \sim 60^{\circ}C)$

Storage Humidity: 5~ 50% @ 70°C, non-condensing (Ambient with Airflow)

The manufacturer introduces the newest product in the Boxer series, SIB-A6523, which utilizes the Intel® AtomTM N2600 processor: this embedded controller expands its graphics performance greatly with the newest generation of AtomTM processors. In this era of information explosion, the advertising of consumer products will not be confined to the family television, but will also spread to high-traffic public areas, like department stores, the bus, transportation station, the supermarket etc. The advertising marketing industry will resort to every conceivable mean to transmit product information to consumers. System integrators will need a multifunction device to satisfy commercial needs for such public advertising. The SIB-A6523 is a standalone high performance controller designed for long-life operation and with high reliability. It can replace traditional methods and become the mainstream controller for the multimedia entertainment market. Specifications

Intel® AtomTM N2600 Dual Core Clock Speed: 1.6 GHz Real Time Clock:

Memory Raivi 1 ype. DDR3 SODIMM BIOS/ Bootloader: AMI BIOS Primary Flash: 1x CFastTM slot Secondary Flash: 2.5 Inch SATA HDD Primary I/O 1x VGA Ethernet: 2x 1 Gig Ethernet with 2x RJ-45 Connector USB: 4x USB 2.0 Ports Serial Ports: 1x RS-232/422/485 3x RS-232 Watchdog: Secondary I/O Keypad: PS/2: Expansion Bus. 1x Mini Card Slot Analog

D/A:

Dimensions

Dimensions: 8.35 × 3.1 × 2.25 in Weight: 8.36 lb Vortage. 9 V Power Misc.: DC power input DC 9-30V w/ 3-pin terminal block

Environmental Low Operating Temperature: -30 C High Operating Temperature: 65 C Environmental Misc.: Operating Temperature With W/T Cfast: -40°F ~ 131°F (-40°C ~ 55°C)

Pricing SLD-A0323-000-R AEC-6523-A1M, Intel Atom N2600, 4x COM, 4x USB2, 2x Gig LAN, VGA \$795.00 Order: 0 Parent Product:

Power Supply: 9-30V DC Disk Interface: SATA

Source URL: https://www.emacinc.com/content/sib-a6523